

# CPW Retrievable Squeeze Packer

## OVERVIEW

Logan's CPW Retrievable Squeeze Packer is designed to perform all the tasks required of a retrievable stimulation and work over packer and withstand high pressures from above or below. It can be used in all types of squeeze cementing, fracturing, and acidizing with subsequent testing.

The hydraulically actuated hold down slips and mechanical lower slips are carbide tipped for long and dependable service. The CPW's packing element system is the proven three-section type, but it is heavier and more reliable than packer systems with an integral bypass.

This packer runs with a separate unloader, such as the Locking Compression Unloader, eliminating the possibility of pumping open that can occur with many equalizing valves.

Size * (in)	Weight (lbs)	Gauge Ring OD (in)	Packer Bore (in)	Connection		
4.00	9.5 – 11.6	3.281	1.50	1.900 EU10Rd		
4.50	13.5 – 16.6	3.640	1.94	2.375 EU8Rd		
	9.5 – 13.5	3.771				
5.00	15 – 18	4.125				
	11.5 – 15	4.250				
5.50	20 – 23	4.500			2.38	2.875 EU8Rd
	14 – 20	4.641				
	13 – 15.5	4.781				
	14 – 20	4.641				
6.625	13 – 15.5	4.781	2.50	2.875 EU8Rd		
	20 – 24	5.750				
7.00	32 – 38	5.969	2.75	3.50 EU8Rd		
	20 – 29					
	17 – 23					
	29 – 38	6.180				
	23 – 29					
	17 – 23					
7.625	33 – 39	6.453	2.50	2.875 EU8Rd		
	24 – 29.7	6.672				
9.625	43.5 – 53.5	8.250	4.00	4.50 EU8Rd		
	32.3 – 43.5	8.500				
	36 – 47	8.438				

\* Larger sizes are available. Special sizes are available upon request.

