



Overview

The Logan EZ Clean™ Ditch Magnet with Rare Earth Elements is the most effective means available to trap and remove metal particles from drilling mud missed by the shale shaker. The ditch magnet will capture all magnetized metals. During milling operations, the magnet is particularly valuable for the removal of mill cuttings and debris that cause wear on mud pumps and other equipment. It eliminates the problems caused by harmful debris returned downhole and is equally effective in both washover and fishing jobs.

Construction

The clean, simple design eliminates the use of trays, gates, and other extra equipment. The magnet is encased in stainless steel and has integral handles at each end for lifting.

Operation

The ditch magnet is most effective when it is suspended by soft line in the mud ditch before the shale shaker, or in the shaker discharge. Depending on milling rate, the unit should be cleaned with fresh or salt water and cuttings wiped away several times per day. The unit may be cleaned less often when cuttings come at a slow rate.

Application

- Removal
- Capture
- Drilling
- Milling
- Completion

SPECIFICATIONS

COMPLETE ASSEMBLY	305-018	305-024	305-036
Length (Inches)	18	24	36

Contact:

Sales and Manufacturing
 Logan Oil Tools, Inc.
 11006 Lucerne Street
 Houston, Texas 77016
 Tel: 281.219.6613
 Fax: 281.219.6638

Email: sales@loganoiltools.com
www.loganinternationalinc.com